



CONVEYING CONFIDENCE™

AN ISO CERTIFIED COMPANY



Endurance Extreme Duty Hydraulic Hose

Extreme duty hydraulic line with **Scuff Tuff** highly abrasion resistant MSHA approved cover. This problem solving hydraulic hose has a compact outside diameter, tight bend radius, and is rated to 1 million impulse cycles.

Endurance Extreme Duty Hydraulic Hose 2SN-K

EXCEEDS DIN EN 857 2SC / SAE 100R16-S

CORE: Oil resistant synthetic rubber

REINFORCEMENT: Two braids of high tensile steel wire. **Exceeds 1 Million Impulse Cycles.**

COVER: **Scuff Tuff** abrasion and ozone resistant synthetic rubber. MSHA approved.

10X the abrasion resistance of a standard hydraulic hose.

TEMPERATURE RANGE: -40 degrees F to +212 degrees F (250 degrees F intermittent)

PART NUMBER	DASH SIZE	NOMINAL HOSE I.D. (INCHES)	NOMINAL HOSE O.D. (INCHES)	WORKING PRESSURE (PSI)	MIN. BURST PRESSURE (PSI)	MIN. BEND RADIUS (INCHES)
72004-80070	-4	0.25	0.53	6,525	26,100	1.77
72005-80070	-5	0.31	0.59	6,090	24,350	2.36
72006-80070	-6	0.38	0.67	5,585	22,340	2.76
72008-80070	-8	0.50	0.82	5,075	20,300	3.54
72010-80070	-10	0.63	0.93	4,250	17,000	5.12
72012-80070	-12	0.75	1.09	4,060	16,240	6.30
72016-80070	-16	1.00	1.40	2,900	11,600	8.27

South St. Paul, Minnesota

305 Bridgepoint Drive
Suite 400
South St. Paul, MN 55075
(651) 645-7522 • info@mnflex.com

Galesburg, Illinois

P.O. Box 1265
698 US Route 150 East
Galesburg, IL 61402
(309) 342-6171

Grand Rapids, Minnesota

19006 River Rd
Grand Rapids, MN 55744
(218) 999-9069

Menomonee Falls, Wisconsin

N83W12650 Stratton Circle
Suite 300
Menomonee Falls, WI 53051
(262) 754-5522



CONVEYING CONFIDENCE™