



CONVEYING CONFIDENCE™

AN ISO CERTIFIED COMPANY



Stalwart Ultra High Pressure Hydraulic Hose

Extreme duty high pressure hydraulic line with a **Scuff Tuff** highly abrasion resistant MSHA approved cover. This flexible multispiral hydraulic hose has a reduced bend radius and force to bend.

Stalwart Ultra High Pressure Hydraulic Hose

MEETS ISO 18752-CC AND EXCEEDS SAE100 R15

CORE: Synthetic rubber, resistant to most hydraulic fluids.

REINFORCEMENT: Four or six spiral layers of high tensile steel wire.

COVER: **Scuff Tuff** abrasion and ozone resistant synthetic rubber. MSHA approved. **10X the abrasion resistance of a standard hydraulic hose.**

TEMPERATURE RANGE: -40 degrees F to +250 degrees F

PART NUMBER	DASH SIZE	NOMINAL HOSE I.D. (INCHES)	NOMINAL HOSE O.D. (INCHES)	WORKING PRESSURE (PSI)	MIN. BURST PRESSURE (PSI)	MIN. BEND RADIUS (INCHES)
72006-80080	-6	0.38	0.79	6,090	24,360	2.56
72008-80080	-8	0.50	0.90	6,090	24,360	3.54
72010-80080	-10	0.63	1.04	6,090	24,360	3.94
72012-80080	-12	0.75	1.21	6,090	24,360	4.72
72016-80080	-16	1.00	1.48	6,090	24,360	5.91
72020-80080	-20	1.25	1.99	6,090	24,360	15.75
72024-80080	-24	1.50	2.26	6,090	24,360	18.11
72032-80080	-32	2.00	2.81	6,090	24,360	21.26

South St. Paul, Minnesota

305 Bridgepoint Drive
Suite 400
South St. Paul, MN 55075
(651) 645-7522 • info@mnflex.com

Galesburg, Illinois

P.O. Box 1265
698 US Route 150 East
Galesburg, IL 61402
(309) 342-6171

Grand Rapids, Minnesota

19006 River Rd
Grand Rapids, MN 55744
(218) 999-9069

Menomonee Falls, Wisconsin

N83W12650 Stratton Circle
Suite 300
Menomonee Falls, WI 53051
(262) 754-5522



CONVEYING CONFIDENCE™